



[Support Center](#) > [Community](#) > [Other Use Cases](#) > ["PRACTICE Stack Overflow" when using GLOBALON PBREAK DO "do\\_something.cmm"](#)

"PRACTICE Stack Overflow" when using GLOBALON PBREAK DO "do\_something.cmm"

**Awaiting Agent**

- NM Neelakantappa M
- **Forum name:** #Other Use Cases

I have registered a event for PBREAK with below cmd:

```
'GLOBALON PBREAK DO "do_something.cmm"'
```

And this breakpoint will be hit too frequently & also in large number.

I have added 'ENDDO' at end of the 'do\_something.cmm' script but problem is there is a 'GO' cmd before 'ENDDO' cmd, because of which 'ENDDO' is not being executed after 'GO'. So, stack is not cleared & also as per my observation with 'PMACRO' window, there were many instances of the above script which were not cleared.

If I remove 'GO', processor will not come out of breakpoint.

below are my needs now:

-> how to execute some cmds in cmm script after 'GO' cmd got executed.

or

-> Is there any options available with 'GLOBALON' cmd to bring processor out of breakpoint

after script got executed

Comment (1)

**Wafi Jmal**

1 month ago

Hello,

In this case you can replace the DO command with a JUMPTO inside a script,for example:

```
GLOBALON PBREAK JUMPTO do_it
```

```
STOP
```

```
do_it:
```

```
...
```

```
Go
```

```
STOP
```

This article may also help you

<https://support.lauterbach.com/kb/articles/practice-stack-overflow-when-using-break-set-address-cmd-do-script-cmm-resume>

Best Regards

Wafi